

Product information  
 Shop-Navcode S29301525  
 Manufacturer Cisco



## Cisco Catalyst 1300-16XTS - Switch

Product information	
Part number	S29301525
Manufacturer	Cisco
Manuf. part number	C1300-16XTS
Main specifications	
Product Description	Cisco Catalyst 1300-16XTS - switch - 16 ports - smart - rack-mountable
Device Type	Switch - 16 ports - L3 - smart
Enclosure Type	Rack-mountable
Subtype	10 Gigabit Ethernet
Ports	8 x 10GBase-T + 8 x 10 Gigabit SFP+
Performance	Forwarding rate (64-byte packets): 238.1 Mpps Switching capacity: 320 Gbps
Capacity	MSTP instances: 8 RPVST+ instances: 126 Link aggregation groups: 8 Link aggregation ports: 8 VLAN IDs: 4093 IGMP multicast groups: 2000 IPv4 routes (static): up to 990 IPv4 interfaces: 128 ACL rules: 1024 Priority queues: 8 Packet buffer size: 1.5 MB
MAC Address Table Size	16000 entries
Jumbo Frame Support	9000 bytes
Routing Protocol	RIP-2, IGMPv2, IGMP, static IP routing, IGMPv3, policy-based routing (PBR), MLDv2, MLD, CIDR, MSTP, RSTP, STP, Bounjour
Remote Management Protocol	SNMP, RMON, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, SSH, SSH-2, CLI, SCP, ICMP, DHCP, RADIUS, Syslog
Features	BOOTP support, VLAN support, IGMP snooping, DoS attack prevention, port mirroring, DiffServ support, Broadcast Storm Control, High Availability, Multicast Storm Control, Unicast Storm Control, sFlow, DHCP snooping, DHCP server, MLD snooping, reset button, STP Root Guard, fanless, DHCP relay, Port Security, DHCP client, IGMP proxy, Protocol-based VLANs support, Storm Control, MLD proxy, IP source guard, ARP inspection, MAC address authentication, IGMP querier, VLAN mirroring, DNS client, VLAN management, LLDP-MED, Private VLAN, RA guard, Guest VLAN, STP loop guard, Energy-Efficient Ethernet (EEE), DSCP based CoS, MAC based VLAN, loopback detection, Telnet server, Telnet client, Unknown Storm Control, BPDU Guard, router advertisement guard, DHCPv6 guard, Q-in-Q tunnelling, IPv4 and IPv6 dual stack, Zero-Touch Deployment, cable length detection, Web authentication, PoE scheduling, trustworthy systems, layer 3 routing, dynamic routing, ACL support, eco-friendly button, Address Resolution Protocol, Auto Surveillance VLAN, CPE VLAN, TCP congestion, iSCSI traffic optimisation, chip guard, boot integrity, persistent PoE, time-based port operation, MSTP support, QoS, PVST+, LACP, GARP, GVRP, ToS, SCP, SCT,

Product information  
 Shop-Navcode S29301525  
 Manufacturer Cisco



## Cisco Catalyst 1300-16XTS - Switch

Main specifications	
	SSD, UDP, DoS protection, WRR, HoL Blocking Prevention, LAG, RPVST+, DAD, LLDP, path MTU discovery, STP support, CLI management, ATP, FHS, IPMB, NDP, RSTP, PVE, MVR, TPID, UDLD, DAI, Cisco NG PnP Protocol, RSPAN
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.1s, IEEE 802.3an, IEEE 802.3at, IEEE 802.3az
Power	AC 100-240 V (50/60 Hz)
Dimensions (WxDxH)	26.8 cm x 27.2 cm x 4.4 cm
Weight	2.49 kg
General	
Device Type	Switch - 16 ports - L3 - smart
Enclosure Type	Rack-mountable
Subtype	10 Gigabit Ethernet
Ports	8 x 10GBase-T + 8 x 10 Gigabit SFP+
Performance	Forwarding rate (64-byte packets): 238.1 Mpps Switching capacity: 320 Gbps
Capacity	MSTP instances: 8 RPVST+ instances: 126 Link aggregation groups: 8 Link aggregation ports: 8 VLAN IDs: 4093 IGMP multicast groups: 2000 IPv4 routes (static): up to 990 IPv4 interfaces: 128 ACL rules: 1024 Priority queues: 8 Packet buffer size: 1.5 MB
MAC Address Table Size	16000 entries
Jumbo Frame Support	9000 bytes
Routing Protocol	RIP-2, IGMPv2, IGMP, static IP routing, IGMPv3, policy-based routing (PBR), MLDv2, MLD, CIDR, MSTP, RSTP, STP, Bounjour
Remote Management Protocol	SNMP, RMON, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, SSH, SSH-2, CLI, SCP, ICMP, DHCP, RADIUS, Syslog
Encryption Algorithm	MD5, SSL
Authentication Method	RADIUS, TACACS+
Features	BOOTP support, VLAN support, IGMP snooping, DoS attack prevention, port mirroring, DiffServ support, Broadcast Storm Control, High Availability, Multicast Storm Control, Unicast Storm Control, sFlow, DHCP snooping, DHCP server, MLD snooping, reset button, STP Root Guard, fanless, DHCP relay, Port Security, DHCP client, IGMP proxy, Protocol-based VLANs support, Storm Control, MLD proxy, IP source guard, ARP inspection, MAC address authentication, IGMP querier, VLAN mirroring, DNS client, VLAN

Product information  
 Shop-Navcode S29301525  
 Manufacturer Cisco



# Cisco Catalyst 1300-16XTS - Switch

<b>General</b>	
	management, LLDP-MED, Private VLAN, RA guard, Guest VLAN, STP loop guard, Energy-Efficient Ethernet (EEE), DSCP based CoS, MAC based VLAN, loopback detection, Telnet server, Telnet client, Unknown Storm Control, BPDU Guard, router advertisement guard, DHCPv6 guard, Q-in-Q tunnelling, IPv4 and IPv6 dual stack, Zero-Touch Deployment, cable length detection, Web authentication, PoE scheduling, trustworthy systems, layer 3 routing, dynamic routing, ACL support, eco-friendly button, Address Resolution Protocol, Auto Surveillance VLAN, CPE VLAN, TCP congestion, iSCSI traffic optimisation, chip guard, boot integrity, persistent PoE, time-based port operation, MSTP support, QoS, PVST+, LACP, GARP, GVRP, ToS, SCP, SCT, SSD, UDP, DoS protection, WRR, HoL Blocking Prevention, LAG, RPVST+, DAD, LLDP, path MTU discovery, STP support, CLI management, ATP, FHS, IPMB, NDP, RSTP, PVE, MVR, TPID, UDLD, DAI, Cisco NG PnP Protocol, RSPAN
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.1s, IEEE 802.3an, IEEE 802.3at, IEEE 802.3az
Processor	X ARM: 1.4 GHz
RAM	1 GB DDR4 SDRAM
Flash Memory	512 MB
Status Indicators	System, PoE, link/activity/speed
<b>Expansion / Connectivity</b>	
Interfaces	8 x 10GBase-T RJ-45 8 x 10GBase-X SFP+ 1 x console RJ-45 1 x USB-C console 1 x USB 1 x RJ-45
<b>Power</b>	
Power Device	Internal power supply
Voltage Required	AC 100-240 V (50/60 Hz)
Power Consumption Operational	50.6 Watt
<b>Miscellaneous</b>	
Included Accessories	Mounting kit, pointer card
MTBF	2,165,105 hours
Compliant Standards	Plug and Play, FCC CFR47 Part 15, WEEE, CSA 22.2, RFC1213, RFC1493, RFC1757, RFC2674, RFC768, RFC791, RFC1157, RFC2460, RFC2011, RFC1643, RFC2012, RFC2013, UL 62368, RFC783, RFC792, RFC2863, RFC793, RFC826, RFC854, RFC2131, RFC2132, RFC1907, RFC1215, RFC2233, RFC2665, RFC951, RFC1542, RFC2618, RFC4443, RFC1981, RFC4861, RFC4862, RFC4291, RFC813, RFC879, RFC896, RFC855, RFC856, RFC858, RFC894, RFC919, RFC920, RFC922, RFC950, RFC1042, RFC1071, RFC1123, RFC1141, RFC1155, RFC1286, RFC1350, RFC1442, RFC1451, RFC1533, RFC1541, RFC1573, RFC1624, RFC1700, RFC1867, RFC2030, RFC2576, RFC2616, RFC2666, RFC2737, RFC2819, RFC3164,



**Medialine EuroTrade AG**  
 Breitlestr. 43  
 55566 Bad Sobernheim

Tel.: +49 6751 85378-0  
 Fax: +49 6751 85378-11

Shop: <http://shop.medialine.ag>  
 Trade register no: HRB 48 73  
 VAT ID No.: DE246410157

Product information  
Shop-Navcode S29301525  
Manufacturer Cisco



## Cisco Catalyst 1300-16XTS - Switch

<b>Miscellaneous</b>	
	RFC3176, RFC3411, RFC3412, RFC3413, RFC3414, RFC3415, RFC3416, RFC4330, RFC4007, RFC3484, RFC5214, RFC4293, RFC3595
<b>Dimensions &amp; Weight</b>	
Width	26.8 cm
Depth	27.2 cm
Height	4.4 cm
Weight	2.49 kg
<b>Environmental Parameters</b>	
Min Operating Temperature	-5 °C
Max Operating Temperature	50 °C
Humidity Range Operating	10 - 90% RH (non-condensing)
Min Storage Temperature	-25 °C
Max Storage Temperature	70 °C
Humidity Range Storage	10 - 90% RH (non-condensing)